

Creating usable living space by making basements dry...



Stylish, warm, living environments from kitchens to saunas, games rooms to home cinema...



Many properties have unused basements and cellars...

With the use of the correct waterproofing system, these can be transformed into wonderful new living spaces.

Converting a damp cellar or basement can be a surprisingly straightforward way of increasing living space and can substantially increase the value of your property.

Waterproofed basements can be converted into kitchens, bathrooms, bedrooms, living rooms, studies, or even home cinemas...
...you are limited only by your imagination.

In commercial premises, common uses for basements include restaurants, bars/nightclubs, additional storage space, retail space, and car parking spaces.

This brochure is intended as an introduction to basement waterproofing and its benefits.

For further details, or to discuss a particular project, please contact our technical department on: 01403 210204 or visit our website at: www.safeguardchem.com



Choosing the right system:

◀ Vandex System
or
Oldroyd System ▶



Either the Vandex System being applied by trowel...



Or the Oldroyd Xv System (applied using sealed fixing plugs)...



The two waterproofing systems...

Safeguard has over twenty years experience in the waterproofing of damp and wet basements. Because the construction methods and degree of dampness found in basements vary considerably, we offer two BBA-approved waterproofing systems for creating a dry basement:

Oldroyd Xv Cavity Drainage Membrane

The Oldroyd Xv system is particularly suited to waterproofing the Victorian basements commonly encountered in the UK as it does not rely on the soundness of the underlying substrate for its effectiveness. The membrane is attached to walls and ceilings by means of special sealed fixing plugs, whilst on the floor there is normally no need for any form of fixing.

The Oldroyd Xv system can be covered with plasterboard, screed, or a floating timber floor. A drainage facility, incorporating a sump and pump, will need to be included as part of the system.

Vandex Waterproof Cement System

The Vandex system is applied to walls, floors, and ceilings using a trowel. The system is particularly useful when waterproofing basements where complicated shapes have to be covered. It is usually the most appropriate system for waterproofing flat ceilings, and has the advantage that a sump and pump are not necessary. However, the Vandex system can only be used on sound, well prepared substrates.

Combination Systems

The best solution is often a combination of the two systems (e.g. Oldroyd Xv applied to floors and walls with the Vandex system used to waterproof a flat ceiling).

Heating and Ventilation

Additional heating and ventilation may be required depending on the proposed use of the basement.

To discuss the most appropriate solution for your basement, call our technical department on: 01403 210204 or visit our website at: www.safeguardchem.com



The finished basement after waterproofing. Now warm and dry.



Making basements dry



Architects and Specifiers

To assist architects in the specification of our basement waterproofing systems, NBS clauses and CAD details are available for both systems. In addition, we offer two RIBA-approved CPD seminars entitled "Waterproofing Existing Basements" and "Waterproofing Basements and Underground Structures (Newbuild)".

Our technical department are able to assist in the specification process, and, on larger projects, site visits can be arranged. Please call: 01403 210204.

Newbuild Basements

Solutions are also available for the waterproofing of new basements during construction.

For details, visit:

www.safeguardchem.com

or call our technical department on:

01403 210204

Installation

We recommend that Safeguard waterproofing products are applied by an experienced waterproofing company.

If you would like a quote for having your basement waterproofed or converted, call: 01403 210204



Redkiln Close . Redkiln Way . Horsham . Sussex . RH13 5QL . UK
T +44 (0) 1403 210204 F +44 (0) 1403 217529 E info@safeguardchem.com
www.safeguardchem.com